

Voluntary Guidelines for

FLOOR-READY
MERCHANDISE

5.0 Hanger Reuse

2nd Edition

Latest Revision: September 15, 2006



Copyright © 1994 - 2006

Voluntary Interindustry Commerce Solutions Association

All rights reserved.

Table of Contents

Section	Title	Page
	Table of Contents	3
	Revision Summary	4
5.0	Hanger Reuse	5
5.1	Introduction	5
5.2	Plastic Properties	5
5.3	Metal Appearance and Finish	5
5.4	Coordinate Loop Dimensions	5
5.5	Hanger Inspections	5
5.6	Package Marking Specifications	5

Revision Summary

Date	Section	Page	Revision
15-Sep-06	All	All	2nd Edition published.

5.0 Hanger Reuse

5.1 Introduction

All approved Hanger Performance Specifications apply to the corresponding reused hanger. Due to the nature of reuse and the fact hangers are introduced to factors outside the manufacturing facilities, the following performance guidelines will address these specific issues.

5.2 Plastic Properties

Stained or excessively scratched hangers will be discarded as unacceptable.

5.3 Metal Appearance & Finish

Metal components will be unacceptable if they are a dark gray color in appearance.

5.4 Coordinate Loop Dimensions

Flat coordinate loops will be acceptable for use with non-coordinate apparel.

5.5 Hanger Inspections

Inspections will be performed to insure that all visual aspects of the VICS reuse hanger performance standards are met.

5.6 Package Marking Specifications

The Packaging and invoicing of a reused hanger be should appropriately labeled by identifying the product as reused and by whom it was processed.